

## ONEAC ON Series® UPS (Power Conditioned Line-Interactive)

ONEAC's power conditioned UPS products feature an isolation transformer-based design, providing full-time protection by removing all harmful power line disturbances. Other manageability enhancement features include: hot-swap battery packs to eliminate battery maintenance downtime and reduce cost. All ON Series e and ON Series m UPS products carry a 5-year warranty on power and control systems and a 2-year warranty on the battery sub-system. Extended warranty programs are available.

#### ONEAC ONePlus Series - Standard Models (60 Hz, 120 V input, 120 V Output)

ONE AC David #	\/A	VA/	Diver	December	Runtime (min)*	Ship Wt	List Duiss
ONEAC Part #	VA	Watts	Plug	Receptacle	Half/Full Load	lb. (kg)	List Price
ONE254AG-SE	250	167	5-15P	(4) 5-15R	0:22/0:08	28 (13)	\$388
ONE404AG-SE	400	265	5-15P	(4) 5-15R	0:14/0:05	28 (13)	\$530
ONE604AG-SE	600	402	5-15P	(8) 5-15R	0:20/0:05	57 (26)	\$765
ONE1004AG-SE	1000	670	5-15P	(8) 5-15R (T)	0:18/0:05	63 (29)	\$998

#### ONEAC ONePlus Series - Standard Models (50/60 Hz, 230 V input, 230 V Output)

					Runtime (min)*	Ship Wt	
ONEAC Part #	VA	Watts	Plug	Receptacle	Half/Full Load	lb. (kg)	List Price
ONE254IG-SE	250	167	IEC 320-C14	(4) IEC 310-C13	0:22/0:08	28 (13)	\$390
ONE404IG-SE	400	265	IEC 320-C14	(4) IEC 310-C13	0:14/0:05	28 (13)	\$535
ONE604IG-SE	600	402	IEC 320-C14	(8) IEC 310-C13	0:20/0:05	57 (26)	\$765
ONE1004IG-SE	1000	670	IEC 320-C14	(8) IEC 310-C13	0:18/0:05	63 (29)	\$1,012

#### ONEAC ON Series e - Standard Models (60 Hz, 120 V input, 120 V Output)

ONEAC Part #	VA	Watts	Plug	Receptacle	Runtime (min)* Half/Full Load	Ship Wt lb. (kg)	List Price
ONE600XA-SB	600	400	5-15P	(4) 5-15R	0:27/0:05	51 (23)	\$1,035.00
ONE600XA-SB1	600	400	5-15P	(4) 5-15R	2:00/0:30	89 (40)	\$1,444.00
ONE600XA-SB2	600	400	5-15P	(4) 5-15R	3:40/1:10	127 (58)	\$1,852.00
ONE600XA-SB3	600	400	5-15P	(4) 5-15R	5:15/2:20	165 (75)	\$2,259.00
ONE600XA-SB4	600	400	5-15P	(4) 5-15R	6:45/3:00	203 (92)	\$2,666.00
ONE600XA-SB5	600	400	5-15P	(4) 5-15R	8:20/3:45	241 (109)	\$3,073.00
ONEXBC-217	ONEAC E	xtended Runtim	e battery cabinet for ONE600		_	38 (17)	\$407.00

ONePlus Series UPS comes with MopUPS Express communications software and Basic and Advanced communications.

The ON Series e UPS comes with Basic communications only.

<sup>\*</sup> Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

<sup>&</sup>quot;X" designates models with extended runtime capabilities. Multiple battery cabinets can be daisy-chained to UPS for extended runtimes.

<sup>&</sup>quot;SB" basic communications interface, standard receptacles.



# ONEAC ON Series® UPS (Power Conditioned Line-Interactive) (continued)

#### ONEAC ON Series e - Wallmount Models (60 Hz, 120 V Input, 120 V Output)

					Runtime (min)*	Ship Wt	
<b>ONEAC Part #</b>	VA	Watts	Plug	Receptacle	Half/Full Load	lb. (kg)	<b>List Price</b>
ONE300XA-W-SB	300	200	5-15P	(2) 5-15R	0:40/0:15	43 (20)	\$780.00
ONE300XA-W-SB1	300	200	5-15P	(2) 5-15R	3:33/1:26	79 (36)	\$1,185.00
ONE300XA-W-SB2	300	200	5-15P	(2) 5-15R	6:49/2:30	115 (52)	\$1,591.00
ONE300XA-W-SB3	300	200	5-15P	(2) 5-15R	10:19/4:10	151(69)	\$1,998.00
ONE300XA-W-SB4	300	200	5-15P	(2) 5-15R	13:45/5:28	187 (85)	\$2,404.00
ONE300XA-W-SB5	300	200	5-15P	(2) 5-15R	17:00/6:16	223 (101)	\$2,810.00
ONE300XA-W-SB6	300	200	5-15P	(2) 5-15R	20:30/7:29	259 (117)	\$3,217.00
ONE300XA-W-SB7	300	200	5-15P	(2) 5-15R	20:30/7:29	295 (134)	\$3,623.00
ONE300XA-W-SV	300	200	5-15P	(2) 5-15R	0:40/0:15	43 (20)	\$749.00
ONE300XA-W-SV1	300	200	5-15P	(2) 5-15R	3:33/1:26	79 (36)	\$1,142.00
ONE300XA-W-SV2	300	200	5-15P	(2) 5-15R	6:49/2:30	115 (52)	\$1,547.00
ONEXBC-W-217	ONEAC S	Standard Extend	ded Runtime battery cabine	et for ON Series e Wal	I-Mount UPSs.	36 (16)	\$407.00

#### ONEAC ON Series e Standard Models (50/60 Hz, 120 V input, 120 V Output)

ONEAC Part #	VA	Watts	Plug	Receptacle	Runtime (min)* Half/Full Load	Ship Wt lb. (kg)	List Price
ONE300J-SV	300	200	5-15P	(4) 5-15R	13/5	37 (16)	\$789.00
ONE300J-SI	300	200	5-15P	(4) 5-15R	13/5	37 (16)	\$862.00

The ON Series e UPS comes with Basic communications only.
\* Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

<sup>&</sup>quot;X" designates models with extended runtime capabilities. Multiple battery cabinets can be daisy-chained to UPS for extended runtimes.

<sup>&</sup>quot;W" or "WL" designates wallmounted models.

<sup>&</sup>quot;SV" no communications interface, standard receptacles.

<sup>&</sup>quot;SB" basic communications interface, standard receptacles.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

The following ON Series UPS models are UL2601/EN60601-1/CSA 22.2 listed, making them suitable for clinical chemistry analysis systems and clinical information systems used in patient area environments.

ONEAC ON Series m Medical Grade - UL60601-1/UL2601, EN60601-1, and CAN/CSA-22.2 No. 601.1-M90 Standard Models - Full Communications (50/60 Hz)

			Input			Runtime (min)*	Ship Wt	
ONEAC Part #	VA	Watts	(Output)	Plug	Receptacle	Half/Full Load	lb. (kg)	List Price
ONM300DA-SI	300	200	120 V	5-15P	(2) 5-15R	40/15	46 (21)	\$882.00
ONM300I-SI	300	200	230 V	IEC**	(4) IEC	16/5	37 (17)	\$800.00
ONM300J-SI	300	200	120 V	IEC**	(4) IEC	16/5	37 (17)	\$788.00
ONM300DI-SI	300	200	230 V	IEC**	(4) IEC	40/15	46 (21)	\$882.00
ONM300DJ-SI	300	200	120 V	IEC**	(4) IEC	40/15	46 (21)	\$867.00
ONM600XA-SI	600	400	120 V	5-15P	(4) 5-15R	27/5	56 (25)	\$1,349.00
ONM600XI-SI	600	400	230 V	IEC**	(4) IEC	27/5	56 (25)	\$1,314.00
ONM600XJ-SI	600	400	120 V	IEC**	(4) IEC	27/5	56 (25)	\$1,355.00
ONMXBC-217	ONEAC E	Extended Ru	untime battery c	abinet for ON	Series m UPS		38 (17)	\$407.00
CA-4CP3S-02	Interface	Cable for O	N Series m UPS	3				\$8.00

<sup>\*</sup> Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

<sup>\*\* 6&#</sup>x27; detachable cord.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

ONEAC's power conditioned UPS products feature an isolation transformer-based design, providing full-time protection by removing all harmful power line disturbances. Other manageability enhancement features include: hot-swap battery packs to eliminate battery maintenance downtime and reduce cost. An OPEN interface option allows you to upgrade easily tomorrow. All ON Series e and ON Series m UPS products carry a 5-year warranty on power and control systems and a 2-year warranty on the battery sub-system. Extended warranty programs are available.

#### ONEAC ON Series Full Communications - Standard Models (60 Hz, 120 V Input, 120 V Output)

					Runtime (min)*	Ship Wt.	
<b>ONEAC Part #</b>	VA	Watts	Plug	Receptacle	Half/Full Load	Lb. (kg)	List Price
ON400A-SN	400	280	5-15P	(4) 5-15R	0:15/0:07	35 (16)	\$872.00
ON600A-SN	600	400	5-15P	(4) 5-15R	0:20/0:10	46 (21)	\$1,113.00
ON900A-SN	900	600	5-15P	(6) 5-15R	0:21/0:09	65 (29)	\$1,372.00
ON1300A-SN	1300	900	5-15P	(8) 5-15R	0:25/0:11	83 (38)	\$1,966.00
ON2000A-SN	1850	1300	5-20P	(8) 5-15R	0:39/0:17	137 (62)	\$2,709.00



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

#### ONEAC ON Series Full Communications - Universal Mount Models (60 Hz, 120 V Input, 120 V Output)

					Runtime (min)*	Ship Wt.	
ONEAC Part #	VA	Watts	Plug	Receptacle	Half/Full Load	Lb. (kg)	<b>List Price</b>
ON700XAU-SN	700	490	5-15P	(8) 5-20R (T)	0:32/0:14	65 (30)	\$1,387
ON700XAU-SN1	700	490	5-15P	(8) 5-20R (T)	2:53/1:15	149 (68)	\$2,127
ON700XAU-SN2	700	490	5-15P	(8) 5-20R (T)	5:55/2:34	233 (105)	\$2,985
ON700XAU-SN3	700	490	5-15P	(8) 5-20R (T)	9:24/4:04	317 (144)	\$3,845
ON700XAU-SN4	700	490	5-15P	(8) 5-20R (T)	13:14/5:44	401 (182)	\$4,707
ON700XAU-SN5	700	490	5-15P	(8) 5-20R (T)	17:21/7:31	485 (220)	\$5,569
ON700XAU-SN6	700	490	5-15P	(8) 5-20R (T)	21:44/9:24	569 (258)	\$6,431
ON700XAU-SN7	700	490	5-15P	(8) 5-20R (T)	26:20/11:24	653 (296)	\$7,293
ON700XAU-SN8	700	490	5-15P	(8) 5-20R (T)	31:08/13:29	737 (334)	\$8,156
ON700XAU-SN9	700	490	5-15P	(8) 5-20R (T)	32:02/14:30	821 (372)	\$9,019
ON700XAU-SN10	700	490	5-15P	(8) 5-20R (T)	34:00/16:35	905 (411)	\$9,882
ON700XAU-SN11	700	490	5-15P	(8) 5-20R (T)	38:18/18:37	989 (449)	\$10,745
ON700XAU-CN	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	0:32/0:14	65 (30)	\$1,267
ON700XAU-CN1	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	2:53/1:15	149 (68)	\$2,114
ON700XAU-CN2	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	5:55/2:34	233 (105)	\$2,968
ON700XAU-CN3	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	9:24/4:04	317 (144)	\$3,826
ON700XAU-CN4	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	13:14/5:44	401 (182)	\$4,685
ON700XAU-CN5	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	17:21/7:31	485 (220)	\$5,546
ON700XAU-CN6	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	21:44/9:24	569 (258)	\$6,407
ON700XAU-CN7	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	26:20/11:24	653 (296)	\$7,269
ON700XAU-CN8	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	31:08/13:29	737 (334)	\$8,131
ON700XAU-CN9	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	32:02/14:30	821 (372)	\$8,993
ON700XAU-CN10	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	34:00/16:35	905 (411)	\$9,856
ON700XAU-CN11	700	490	L5-20P	(1) L5-20R & (4) 5-20R (T)	38:18/18:37	989 (449)	\$10,718
ONXBCU-417	ONEAC Sta Mount UPS		d Runtime battery cabinet for 0	ON700, ON1000 UPS, ON150	0 and ON2000 Universal	84 (38)	\$863.00

<sup>\*</sup> Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

All ON Series Models have basic and advanced communications capabilities.

The ON Series Universal Mount UPSs include MopUPSPROFESSIONAL software and cable.

Receptacles with (T) refers to "T-Slot" output connector and will accept either 1-15P or 5-20P plugs

<sup>&</sup>quot;X" designates models with extended runtime capabilities. Multiple battery cabinets can be daisy-chained to UPS for extended runtimes

<sup>&</sup>quot;U" designates universal mount (vertical, horizontal, rack).

<sup>&</sup>quot;SN" designates interface is capable of either Basic or Advanced Communications.

For UPS Communications, Software, and Accessories see page 17.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

#### ONEAC ON Series Full Communications - Universal Mount Models (60 Hz, 120 V Input, 120 V Output)

					Runtime (min)*	Ship Wt.	
ONEAC Part #	VA	Watts	Plug	Receptacle	Half/Full Load	Lb. (kg)	List Price
ON1000XAU-SN	1000	700	5-15P	(8) 5-20R (T)	0:21/0:09	65 (30)	\$1,554.00
ON1000XAU-SN1	1000	700	5-15P	(8) 5-20R (T)	1:53/0:48	149 (68)	\$2,426.00
ON1000XAU-SN2	1000	700	5-15P	(8) 5-20R (T)	3:52/1:38	233 (105)	\$3,294.00
ON1000XAU-SN3	1000	700	5-15P	(8) 5-20R (T)	6:09/2:26	317 (144)	\$4,165.00
ON1000XAU-SN4	1000	700	5-15P	(8) 5-20R (T)	8:39/3:40	401 (182)	\$5,033.00
ON1000XAU-SN5	1000	700	5-15P	(8) 5-20R (T)	11:21/4:48	485 (220)	\$5,901.00
ON1000XAU-SN6	1000	700	5-15P	(8) 5-20R (T)	14:13/6:01	569 (258)	\$6,773.00
ON1000XAU-SN7	1000	700	5-15P	(8) 5-20R (T)	17:13/7:18	653 (296)	\$7,644.00
ON1000XAU-SN8	1000	700	5-15P	(8) 5-20R (T)	20:21/8:37	737 (334)	\$8,516.00
ON1000XAU-SN9	1000	700	5-15P	(8) 5-20R (T)	20:51/9:39	821 (372)	\$9,384.00
ON1000XAU-SN10	1000	700	5-15P	(8) 5-20R (T)	23:46/11:00	905 (411)	\$10,255.00
ON1000XAU-SN11	1000	700	5-15P	(8) 5-20R (T)	26:46/12:24	989 (449)	\$11,123.00
ON1000XAU-CN	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	0:21/0:09	65 (30)	\$1,762.00
ON1000XAU-CN1	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	1:53/0:48	149 (68)	\$2,632.00
ON1000XAU-CN2	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	3:52/1:38	233 (105)	\$3,500.00
ON1000XAU-CN3	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	6:09/2:26	317 (144)	\$4,372.00
ON1000XAU-CN4	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	8:39/3:40	401 (182)	\$5,243.00
ON1000XAU-CN5	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	11:21/4:48	485 (220)	\$6,111.00
ON1000XAU-CN6	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	14:13/6:01	569 (258)	\$6,983.00
ON1000XAU-CN7	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	17:13/7:18	653 (296)	\$7,851.00
ON1000XAU-CN8	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	20:21/8:37	737 (334)	\$8,722.00
ON1000XAU-CN9	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	20:51/9:39	821 (372)	\$9,594.00
ON1000XAU-CN10	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	23:46/11:00	905 (411)	\$10,462.00
ON1000XAU-CN11	1000	700	L5-20P	(1) L5-20R & (4) 5-20R (T)	26:46/12:24	989 (449)	\$11,332.00
ONXBCU-417	ONEAC Sta Mount UPS		ed Runtime battery cabinet for 0	ON700, ON1000 UPS, ON150	0 and ON2000 Universal	84 (38)	\$863.00

<sup>\*</sup> Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

Receptacles with (T) refers to "T-Slot" output connector and will accept either 1-15P or 5-20P plugs

All ON Series Models have basic and advanced communications capabilities.

The ON Series Universal Mount UPSs include MopUPSPROFESSIONAL software and cable.

<sup>&</sup>quot;X" designates models with extended runtime capabilities. Multiple battery cabinets can be daisy-chained to UPS for extended runtimes

<sup>&</sup>quot;U" designates universal mount (vertical, horizontal, rack).

<sup>&</sup>quot;SN" designates interface is capable of either Basic or Advanced Communications.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

#### ONEAC ON Series Full Communications - Universal Mount Models (60 Hz, 120 V Input, 120 V Output)

ONEAC Part #	VA	Watts	Plug	Receptacle	Runtime (min)* Half/Full Load	Ship Wt. Lb. (kg)	List Price
ON1500XAU-SN	1440	1000	5-15P	(8) 5-20R (T)	0:13/0:05	71 (32)	\$1,969
ON1500XAU-SN1	1440	1000	5-15P	(8) 5-20R (T)	1:17/0:31	155 (70)	\$2,767
ON1500XAU-SN2	1440	1000	5-15P	(8) 5-20R (T)	2:40/1:04	239 (108	\$3,637
ON1500XAU-SN3	1440	1000	5-15P	(8) 5-20R (T)	4:16/1:42	323 (147)	\$4,505
ON1500XAU-SN4	1440	1000	5-15P	(8) 5-20R (T)	6:01/2:24	407 (185)	\$5,376
ON1500XAU-SN5	1440	1000	5-15P	(8) 5-20R (T)	7:54/3:09	491 (575)	\$6,248
ON1500XAU-SN6	1440	1000	5-15P	(8) 5-20R (T)	9:54/3:57	575 (261)	\$7,119
ON1500XAU-SN7	1440	1000	5-15P	(8) 5-20R (T)	12:00/4:48	659 (299)	\$7,987
ON1500XAU-SN8	1440	1000	5-15P	(8) 5-20R (T)	14:12/5:40	743 (337)	\$8,859
ON1500XAU-SN9	1440	1000	5-15P	(8) 5-20R (T)	16:29/6:35	827 (375)	\$9,727
ON1500XAU-SN10	1440	1000	5-15P	(8) 5-20R (T)	18:51/7:32	911 (413)	\$10,598
ON1500XAU-SN11	1440	1000	5-15P	(8) 5-20R (T)	21:17/8:30	995 (451)	\$11,466
ON1500XAU-CN	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	0:13/0:05	71 (32)	\$1,956
ON1500XAU-CN1	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	1:17/0:31	155 (70)	\$2,975
ON1500XAU-CN2	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	2:40/1:04	239 (108	\$3,847
ON1500XAU-CN3	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	4:16/1:42	323 (147)	\$4,718
ON1500XAU-CN4	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	6:01/2:24	407 (185)	\$5,586
ON1500XAU-CN5	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	7:54/3:09	491 (575)	\$6,458
ON1500XAU-CN6	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	9:54/3:57	575 (261)	\$7,326
ON1500XAU-CN7	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	12:00/4:48	659 (299)	\$8,194
ON1500XAU-CN8	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	14:12/5:40	743 (337)	\$9,065
ON1500XAU-CN9	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	16:29/6:35	827 (375)	\$9,937
ON1500XAU-CN10	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	18:51/7:32	911 (413)	\$10,805
ON1500XAU-CN11	1440	1000	L5-20P	(1) L5-20R & (4) 5-20R (T)	21:17/8:30	995 (451)	\$11,676
ONXBCU-417		Standard Extend Universal Moun		net for ON700, ON1000 U	JPS, ON1500 and	84 (38)	\$863.00

<sup>\*</sup> Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

All ON Series Models have basic and advanced communications capabilities.

The ON Series Universal Mount UPSs include MopUPSPROFESSIONAL software and cable

Receptacles with (T) refers to "T-Slot" output connector and will accept either 1-15P or 5-20P plugs

<sup>&</sup>quot;X" designates models with extended runtime capabilities. Multiple battery cabinets can be daisy-chained to UPS for extended runtimes

<sup>&</sup>quot;U" designates universal mount (vertical, horizontal, rack).

<sup>&</sup>quot;SN" designates interface is capable of either Basic or Advanced Communications.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

#### ONEAC ON Series Full Communications - Universal Mount Models (60 Hz, 120 V Input, 120 V Output)

					Runtime (min)*	Ship Wt.	
ONEAC Part #	VA	Watts	Plug	Receptacle	Half/Full Load	Lb. (kg)	List Price
ON2000XAU-SN	1920	1345	5-20P	(8) 5-20R (T)	0:15/0:06	112 (51)	\$3,054
ON2000XAU-SN1	1920	1345	5-20P	(8) 5-20R (T)	0:55/0:24	196 (89)	\$3,812
ON2000XAU-SN2	1920	1345	5-20P	(8) 5-20R (T)	1:44/0:45	280 (127)	\$4,688
ON2000XAU-SN3	1920	1345	5-20P	(8) 5-20R (T)	2:40/1:10	364 (165)	\$5,559
ON2000XAU-SN4	1920	1345	5-20P	(8) 5-20R (T)	3:42/1:36	448 (206)	\$6,425
ON2000XAU-SN5	1920	1345	5-20P	(8) 5-20R (T)	4:48/2:05	532 (241)	\$7,293
ON2000XAU-SN6	1920	1345	5-20P	(8) 5-20R (T)	5:58/2:35	616 (279)	\$8,157
ON2000XAU-SN7	1920	1345	5-20P	(8) 5-20R (T)	7:11/3:07	700 (318)	\$9,024
ON2000XAU-SN8	1920	1345	5-20P	(8) 5-20R (T)	8:27/3:40	784 (326)	\$9,887
ON2000XAU-SN9	1920	1345	5-20P	(8) 5-20R (T)	9:46/4:14	868 (394)	\$10,754
ON2000XAU-SN10	1920	1345	5-20P	(8) 5-20R (T)	11:08/4:50	952 (432)	\$11,618
ON2000XAU-SN11	1920	1345	5-20P	(8) 5-20R (T)	12:33/5:27	1036 (470)	\$12,482
ON2000XAU-TN	1920	1345	L5-20P	(4) L5-15R & (4) 5-20R (T)	0:15/0:06	112 (51)	\$2,856
ON2000XAU-CN	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	0:15/0:06	112 (51)	\$2,927
ON2000XAU-CN1	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	0:55/0:24	196 (89)	\$3,802
ON2000XAU-CN2	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	1:44/0:45	280 (127)	\$4,676
ON2000XAU-CN3	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	2:40/1:10	364 (165)	\$5,543
ON2000XAU-CN4	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	3:42/1:36	448 (206)	\$6,412
ON2000XAU-CN5	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	4:48/2:05	532 (241)	\$7,280
ON2000XAU-CN6	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	5:58/2:35	616 (279)	\$8,143
ON2000XAU-CN7	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	7:11/3:07	700 (318)	\$9,006
ON2000XAU-CN8	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	8:27/3:40	784 (326)	\$10,270
ON2000XAU-CN9	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	9:46/4:14	868 (394)	\$10,735
ON2000XAU-CN10	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	11:08/4:50	952 (432)	\$11,603
ON2000XAU-CN11	1920	1345	L5-20P	(2) L5-20R & (4) 5-20R (T)	12:33/5:27	1036 (470)	\$12,467
ONXBCU-417		Standard Extend Universal Moun		inet for ON700, ON1000 U	IPS, ON1500 and	84 (38)	\$863.00



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

#### ONEAC ON Series Full Communications - Universal Mount Models (60 Hz, 208/230 V Input, 230/120 V Output)

					Runtime (min)*	Ship Wt.	
<b>ONEAC Part #</b>	VA	Watts	Plug	Receptacle	Half/Full Load	Lb. (kg)	List Price
ON3000XAU-SN1	3000	2100	L6-20P	(9) 5-20T & (3) L6-20R	0	225 (102)	\$3,890
ON3000XAU-SN2	3000	2100	L6-20P	(9) 5-20T & (3) L6-20R	0	310 (141)	\$4,785
ON3000XAU-SN3	3000	2100	L6-20P	(9) 5-20T & (3) L6-20R	0	395 (179)	\$5,679
ON3000XAU-SN4	3000	2100	L6-20P	(9) 5-20T & (3) L6-20R	0	480 (218)	\$6,571
ON3000XAU-SN5	3000	2100	L6-20P	(9) 5-20T & (3) L6-20R	0	565 (256)	\$7,464
ON3000XAU-SN6	3000	2100	L6-20P	(9) 5-20T & (3) L6-20R	0	650 (295)	\$8,356
ON3000XAU-SN7	3000	2100	L6-20P	(9) 5-20T & (3) L6-20R	0	735 (333)	\$9,248
ON3000XAU-SN8	3000	2100	L6-20P	(9) 5-20T & (3) L6-20R	0	820 (372)	\$10,015
ON3000XAU-30SN1	3000	2100	L6-30P	(9) 5-20T & (3) L6-30R	0	225 (102)	\$3,886
ON3000XAU-30SN2	3000	2100	L6-30P	(9) 5-20T & (3) L6-30R	0	310 (141)	\$4,784
ON3000XAU-30SN3	3000	2100	L6-30P	(9) 5-20T & (3) L6-30R	0		\$5,677
ON3000XAU-30SN4	3000	2100	L6-30P	(9) 5-20T & (3) L6-30R	0	480 (218)	\$6,570
ON3000XAU-30SN5	3000	2100	L6-30P	(9) 5-20T & (3) L6-30R	0	565 (256)	\$7,463
ON3000XAU-30SN6	3000	2100	L6-30P	(9) 5-20T & (3) L6-30R	0	650 (295)	\$8,355
ON3000XAU-30SN7	3000	2100	L6-30P	(9) 5-20T & (3) L6-30R	0	735 (333)	\$9,247
ON3000XAU-30SN8	3000	2100	L6-30P	(9) 5-20T & (3) L6-30R	0	820 (372)	\$10,014
ONXBCU-2X217	ONEAC S	Standard Exter	nded Runtime battery cabi	net for ON3000 Universal	Mount UPS.	83 (38)	\$950

<sup>\*</sup>Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

Receptacles with (T) refers to "T-Slot" output connector and will accept either 1-15P or 5-20P plugs

All ON Series Models have basic and advanced communications capabilities.

The ON Series Universal Mount UPSs include MopUPSPROFESSIONAL software and cable.

<sup>&</sup>quot;X" designates models with extended runtime capabilities. Multiple battery cabinets can be daisy-chained to UPS for extended runtimes

<sup>&</sup>quot;U" designates universal mount (vertical, horizontal, rack).

<sup>&</sup>quot;SN" designates interface is capable of either Basic or Advanced Communications.

For UPS Communications, Software, and Accessories see page 17.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

ONEAC ON Series Full Communications - Extended Runtime Models (60 Hz, 120 V Input, 120 V Output or 208-240 V Input, 115-230 V Output)

			Input			Runtime (min)*	Ship Wt.	
ONEAC Part #	VA	Watts	(Output)	Plug	Receptacle	Half/Full Load	Lb. (kg)	List Price
			208/240 V		(2) L6-30R and			
ON2200XA-SN	2200	1500	(115-230 V)	L6-30P	(4) 5-20R	0	82 (37)	\$2,543.00
			208/240 V		(2) L6-30R and			
ON2200XA-SNK	2200	1500	(115-230 V)	L6-30P	(4) 5-20R	32/13	157 (71)	\$3,366.00
			208/240 V		(2) L6-30R &			
ON2200XA-SNTK	2200	1500	(115-230 V)	L6-30P	(4) 5-20R	32/13	160 (73)	\$3,364.00
ONXBC-417	ONEAC E	xtended R	untime Battery (	Cabinet for Star	ndard ON Series e UPS	Contact ONEAC	75 (34)	\$869.00

#### ONEAC ON Series Full Communications - Wallmount Models (60 Hz, 120 V Input and 120 V Output)

					Runtime (min)*	Ship Wt.	
ONEAC Part #	VA	Watts	Plug	Receptacle	Half/Full Load	Lb. (kg)	List Price
ON400XA-WL-SNK	400	280	5-15P	(4) 5-15R	1:53/0:55	70 (32)	\$1,405.00
ON400XA-WSNK2	400	280	5-15P	(4) 5-15R	3:56/2:00	110 (50)	\$2,995.00
ON400XA-WSNK3	400	280	5-15P	(4) 5-15R	6:03/3:16	150 (68)	\$4,045.00
ON400XA-WSNK4	400	280	5-15P	(4) 5-15R	8:25/4:29	190 (86)	\$5,022.00
ON400XA-WSNK5	400	280	5-15P	(4) 5-15R	10:24/5:29	230 (104)	\$5,999.00
ON400XA-WSNK6	400	280	5-15P	(4) 5-15R	12:30/6:33	270 (123)	\$6,920.00
ON400XA-WSNK7	400	280	5-15P	(4) 5-15R	15:05/7:54	310 (141)	\$8,421.00
ON600XA-WL-SNK	600	400	5-15P	(4) 5-15R	1:17/0:29	74 (34)	\$1,385.00
ON600XA-WSNK2	600	400	5-15P	(4) 5-15R	2:43/1:11	114 (52)	\$1,840.00
ON600XA-WSNK3	600	400	5-15P	(4) 5-15R	4:18/2:03	154 (70)	\$2,292.00
ON600XA-WSNK4	600	400	5-15P	(4) 5-15R	5:57/2:47	194 (88)	\$2,743.00
ON600XA-WSNK5	600	400	5-15P	(4) 5-15R	7:18/3:22	234 (106)	\$3,194.00
ON600XA-WSNK6	600	400	5-15P	(4) 5-15R	8:53/3:50	274 (124)	\$3,644.00
ON600XA-WSNK7	600	400	5-15P	(4) 5-15R	10:41/3:50	314(142)	\$4,094.00
ON600XA-WSNK8	600	400	5-15P	(4) 5-15R	10:41/4:42	354 (161)	\$4,544.00
ONXBC-WL-217	ONEAC V	Vallmount Ex	tended Runtime Battery Cabinet		Contact ONEAC	40 (18)	\$585.00

<sup>\*</sup> Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

All ON Series Models have basic and advanced communications capabilities.

<sup>&</sup>quot;W" or "WL" designates wallmounted models.

<sup>&</sup>quot;SN" designates interface is capable of either Basic or Advanced Communications.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

ONEAC's power conditioned UPS products feature an isolation transformer-based design, providing full-time protection by removing all harmful power line disturbances. Other manageability enhancement features include: hot-swap battery packs to eliminate battery maintenance downtime and reduce cost. An OPEN interface option allows you to upgrade easily tomorrow. All ON Series e UPS products carry a 5-year warranty on power and control systems and a 2-year warranty on the battery sub-system. Extended warranty programs are available.

#### ONEAC ON Series Full Communications - Standard Models (50/60 Hz, 120 V Input and 120 V Output)

ONEAC Part #	VA	Watts	Plug	Receptacle	Runtime (min)* Half/Full Load	Ship Wt. lbs. (kg)	List Price
ON400J-SN	400	280	IEC	(4) IEC	15/7	35 (16)	\$1,054.00
ON900J-SN	900	600	IEC	(4) IEC	22/7	67 (30)	\$1,560.00

#### ONEAC ON Series Full Communications - Standard Models (50/60 Hz, 230 V Input and 230 V Output)

					Runtime (min)*	Ship Wt.	
ONEAC Part #	VA	Watts	Plug	Receptacle	Half/Full Load	lbs. (kg)	List Price
ON400I-SN	400	280	IEC	(4) IEC	15/7	35 (16)	\$1,005.00
ON600I-SN	600	400	IEC	(4) IEC	20/8	44 (20)	\$1,174.00
ON1300I-SN	1300	900	IEC	(8) IEC	27/8	95 (43)	\$2,150.00
ON2000I-SN	2000	1300	IEC	(8) IEC	37/15	137 (62)	\$2,987.00

#### ONEAC ON Series Full Communications - Extended Runtime Models (50/60 Hz, 230 V Input and 230 V Output)

ONEAC Part #	VA	Watts	Plug	Receptacle	Runtime (min)* Half/Full Load	Ship Wt. Ibs. (kg)	List Price
ON700XIU-SN	700	470	IEC	(8) IEC	0:32/0:14	71 (32)	\$1,511.00
ON1000XIU-SN	1000	670	IEC	(8) IEC	0:21/0:09	71 (32)	\$1,807.00
ON1500XIU-SN	1440	1000	IEC	(8) IEC	0:13/0:05	73 (33)	\$2,393.00
ON2000XIU-SN	1920	1345	IEC	(8) IEC	0:14/0:06	121 (55)	\$3,576.00
	ONEAC S	Standard Extended	Runtime battery cabine	t for ON700, ON1000	UPS, ON1500 and		
ONXBCU-417	ON2000 l	Jniversal Mount U	PSs.			84 (38)	\$863.00

<sup>\*</sup> Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

All ON Series Models have basic and advanced communications capabilities.

<sup>&</sup>quot;X" designates models with extended runtime capabilities. Multiple battery cabinets can be daisy-chained to UPS for extended runtimes

<sup>&</sup>quot;U" designates universal mount (vertical, horizontal, rack).

<sup>&</sup>quot;RM" designates rackmounted models, 2-post.

For UPS Communications, Software, and Accessories see page 17.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

# ONEAC ON Series Full Communications - Wallmount Extended Runtime Models (50/60 Hz, 230 V Input and 230 V Output)

ONEAC Part #	VA	Watts	Plug	Receptacle	Runtime (min)* Half/Full Load	Ship Wt. Ibs. (kg)	List Price
ON400XI-WL-SNK	400	280	IEC	(4) IEC	113/55	70 (32)	\$1,566.00
ON600XI-WL-SNK	600	400	IEC	(4) IEC	77/29	80 (36)	\$1,537.00
ONXBC-WL-217	Wallmour	nt Extended Ru	intime Battery Cabinet			40 (18)	\$585.00

<sup>\*</sup> Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

All ON Series Models have basic and advanced communications capabilities.

<sup>&</sup>quot;U" designates universal mount (vertical, horizontal, rack).

<sup>&</sup>quot;W" or "WL" designates wallmounted models.

<sup>&</sup>quot;RM" designates rackmounted models, 2-post.

For UPS Communications, Software, and Accessories see page 17.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

ONEAC's power conditioned UPS products feature an isolation transformer-based design, providing full-time protection by removing all harmful power line disturbances. The ON Series 3300 VA - 5000 VA UPS incorporates unique service and maintenance features as standard. A number of optional features are also available. All ON Series UPS products carry a 5-year warranty on power and control systems and a 2-year warranty on the battery sub-system. Extended warranty programs are available.

ON Series Full Communications (for Nortel PBX Apps) (60 Hz, 208/220-240 V input, 120/208 V or 120/220-240 V output) this product will be discontinued October 2007.

The following systems are UL approved and include a power head, battery cabinet on a wheeled base (batteries can be added for increased runtime), a full maintenance bypass for hot-swap of power and control modules, a remote power-off interface, an 8' Nortel Meridian interface cable and ground bar.

maintenance bypass for	not ottap of p	ower and control in	saules , a formete peri	or on interface, are a	Runtime (min)**	Ship Wt.	aria bar.
ONEAC Part #	VA	Watts	Plug	Receptacle	Half/Full Load	lbs. (kg)	<b>List Price</b>
ONIGOGONITO	2022	0000	1.0.000	(3) L6-30R and	**	075 (470)	<b>#0.000</b>
ON3300NT0	3300	2200	L6-30P	(4) 5-15R (3) L6-30R and		375 (170)	\$8,029
ON3300NT1	3300	2200	L6-30P	(4) 5-15R	47/21	593 (269)	\$11,871
01033001011	3300	2200	LU-30F	(3) L6-30R and	71/21	393 (209)	φ11,071
ON3300NT2	3300	2200	L6-30P	(4) 5-15R	118/53	731 (332)	\$11,826
				(3) L6-30R and		- ( )	+ ,
ON3300NT4	3300	2200	L6-30P	(4) 5-15R	295/226	1087 (493)	\$16,010
				(3) L6-30R and			
ON3300NT6	3300	2200	L6-30P	(4) 5-15R	504/226	1592 (722)	\$16,625
ONIGOGONITO	0000	0000	10.000	(3) L6-30R and	707/004	4040 (004)	<b>#</b> 40 500
ON3300NT8	3300	2200	L6-30P	(4) 5-15R (3) L6-30R and	737/331	1948 (884)	\$18,503
ON3300NT10	3300	2200	L6-30P	(3) L6-30R and (4) 5-15R	989/444	2304 (1045)	\$21,897
010330010110	3300	2200	LU-30F	(3) L6-30R and	303/444	2304 (1043)	φ21,091
ON3305NT0	3300*	2200	6-50P	(4) 5-15R	**	405 (184)	\$9,106
0.10000.110			0 00.	(3) L6-30R and		.00 (.0.)	ψο,
ON3305NT1	3300*	2200	6-50P	(4) 5-15R	47/21	623 (283)	\$12,320
				(3) L6-30R and		· · · · · · · · · · · · · · · · · · ·	
ON3305NT2	3300*	2200	6-50P	(4) 5-15R	118/53	761 (345)	\$12,512
011000=11 <del>=</del> 4				(3) L6-30R and	005/400	( )	<b>*</b>
ON3305NT4	3300*	2200	6-50P	(4) 5-15R (3) L6-30R and	295/132	1117 (507)	\$16,705
ON3305NT6	3300*	2200	6-50P	(3) L6-30R and (4) 5-15R	504/226	1622 (736)	\$17,303
010330310116	3300	2200	0-30F	(3) L6-30R and	304/220	1022 (730)	\$17,303
ON3305NT8	3300*	2200	6-50P	(4) 5-15R	737/331	1978 (879)	\$19,194
<u> </u>			0 00.	(3) L6-30R and		.0.0 (0.0)	Ψ.ο,.ο.
ON3305NT10	3300*	2200	6-50P	(4) 5-15R	989/444	2334 (1054)	\$22,094
				(3) L6-30R and		· · · · · · · · ·	
ON5000NT0	5000	3400	6-50P	(4) 5-15R	**	405 (184)	\$10,613
C)   = 0 C)   = 1		0.400		(3) L6-30R and	00/40	222 (222)	<b>*</b> • • • • • •
ON5000NT1	5000	3400	6-50P	(4) 5-15R	30/12	623 (283)	\$12,387
ON5000NT2	5000	3400	6-50P	(3) L6-30R and (4) 5-15R	75/30	761 (345)	\$13,772
ON3000N12	5000	3400	0-3UF	(3) L6-30R and	73/30	761 (343)	φ13,772
ON5000NT4	5000	3400	6-50P	(4) 5-15R	191/76	1117 (507)	\$17,981
30000111 T	0000	0.00	0 001	(3) L6-30R and		(007)	ψ17,001
ON5000NT6	5000	3400	6-50P	(4) 5-15R	327/131	1622 (736)	\$18,579
<u>;</u>				(3) L6-30R and		. ,	· · ·
ON5000NT8	5000	3400	6-50P	(4) 5-15R	477/191	1978 (879)	\$20,516
01/T0001/T10				(3) L6-30R and	0.44/057		
ON5000NT10	5000	3400	6-50P	(4) 5-15R	641/257	2334 (1054)	\$23,095

<sup>\*</sup> These models are hot-swap, field-upgradeable to 5000 VA.

<sup>\*\*</sup> To add runtime, see battery cabinet information on page 15. Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

All ON Series Models have basic and advanced communications capabilities.

<sup>&</sup>quot;NT" designates models suitable for Nortel PBX apps (includes isolated contact interface card and 8 ft. cable to connect ONEAC system monitor port to the column of PBX)

<sup>^</sup> Full maintenance bypass allows hot-swap of both the control and power modules.

ONEAC ON Series 3300/3305/5000 systems are shipped on pallets 51" (H) x 27" (W) x 32" (D)

For ON Series 3.3 and 5.0 kVA UPS Options and Accessories, see page 16.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

ONEAC ON Series (Quad Duplex) Full Comm. (60 Hz, 208/220-240 V input, 120/208 V or 120/220-240 V output) This product will be discontinued October 2007.

The following systems are UL approved and include a power head, battery cabinet on a wheeled base (batteries can be added for increased runtime), hardwired input and output connections, a full maintenance bypass for hot-swap of power and control modules^, a remote power-off interface and ground bar.

ONEAC Part #	VA	Watts	Plug	Receptacles	Runtime (min)** Half/Full Load	Ship Wt. Lb. (kg)	List Price
ON3300A8S0	3300	2200	L6-30P	(1) L6-30R and (8) 5-15R	**	375 (170)	\$7,950
ON3300A8S1	3300	2200	L6-30P	(1) L6-30R and (8) 5-15R	47/21	593 (269)	\$11,791
ON3300A8S2	3300	2200	L6-30P	(1) L6-30R and (8) 5-15R	118/53	731 (332)	\$11,747
ON3300A8S4	3300	2200	L6-30P	(1) L6-30R and (8) 5-15R	295/132	1078 (489)	\$15,874
ON3300A8S6	3300	2200	L6-30P	(1) L6-30R and (8) 5-15R	504/226	1592 (722)	\$16,546
ON3300A8S8	3300	2200	L6-30P	(1) L6-30R and (8) 5-15R	737/331	1948 (884)	\$18,422
ON3300A8S10	3300	2200	L6-30P	(1) L6-30R and (8) 5-15R	989/444	2304 (1045)	\$21,860
ON3305A8S0	3300*	2200	6-50P	(1) L6-30R and (8) 5-15R	**	405 (184)	\$9,029
ON3305A8S1	3300*	2200	6-50P	(1) L6-30R and (8) 5-15R	47/21	623 (283)	\$12,385
ON3305A8S2	3300*	2200	6-50P	(1) L6-30R and (8) 5-15R	118/53	761 (345)	\$12,435
ON3305A8S4	3300*	2200	6-50P	(1) L6-30R and (8) 5-15R	295/132	1117 (507)	\$16,628
ON3305A8S6	3300*	2200	6-50P	(1) L6-30R and (8) 5-15R	504/226	1622 (737)	\$17,227
ON3305A8S8	3300*	2200	6-50P	(1) L6-30R and (8) 5-15R	737/331	1978 (897)	\$19,115
ON3305A8S10	3300*	2200	6-50P	(1) L6-30R and (8) 5-15R	989/444	2334 (1059)	\$22,118
ON5000A8S0	5000	3400	6-50P	(1) L6-30R and (8) 5-15R	**	405 (184)	\$10,533
ON5000A8S1	5000	3400	6-50P	(1) L6-30R and (8) 5-15R	30/12	623 (283)	\$10,560
ON5000A8S2	5000	3400	6-50P	(1) L6-30R and (8) 5-15R	75/30	761 (345)	\$13,611
ON5000A8S4	5000	3400	6-50P	(1) L6-30R and (8) 5-15R	191/76	1117 (507)	\$17,903
ON5000A8S6	5000	3400	6-50P	(1) L6-30R and (8) 5-15R	327/131	1622 (736)	\$18,502
ON5000A8S8	5000	3400	6-50P	(1) L6-30R and (8) 5-15R	477/191	1978 (897)	\$20,435
ON5000A8S10	5000	3400	6-50P	(1) L6-30R and (8) 5-15R	641/257	2334 (1059)	\$30,191
							<del>+, +-</del>

 $<sup>^{\</sup>star}$  These models are hot-swap, field-upgradeable to 5000 VA.

<sup>\*\*</sup> To add runtime, see battery cabinet information on page 15. Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

<sup>^</sup>Full maintenance bypass allows hot-swap of both the control and power modules

All ON Series Models have basic and advanced communications capabilities.

ONEAC ON Series 3300/3305/5000 systems are shipped on pallets  $\dot{5}$ 1" (H) x 27" (W) x 32" (D)

For UPS Communications, Software, and Accessories see page 17.

For ON Series 3.3 and 5.0 kVA UPS Options and Accessories, see page 16.



### **ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)**

ONEAC ON Series (Hardwired in/out) Full Communications - (60 Hz, 208/230 V Input, 115/230 V Output) This product will be discontinued October 2007.

The following systems are UL approved and include a power head, battery cabinet on a wheeled base (batteries can be added for increased runtime), hardwired input and output connections, a full maintenance bypass for hot-swap of power and control modules, a remote power-off interface and groundbar.

		,			Runtime (min)**		
ONEAC Model #	VA	Watts	Plug	Receptacles	Half/Full Load	Lb. (kg)	List Price
ON3300AHW0	3300	2200	HW	HW	**	375 (170)	\$7,285
ON3300AHW1	3300	2200	HW	HW	47/21	593 (369)	\$11,553
ON3300AHW2	3300	2200	HW	HW	118/53	731 (332)	\$11,517
ON3300AHW4	3300	2200	HW	HW	295/132	1087 (493)	\$15,694
ON3300AHW6	3300	2200	HW	HW	504/226	1592 (722)	\$16,301
ON3300AHW8	3300	2200	HW	HW	737/331	1948 (884)	\$18,161
ON3300AHW10	3300	2200	HW	HW	989/444	2304 (1045)	\$20,700
ON3305AHW0	3300*	2200	HW	HW	**	405 (184)	\$8,329
ON3305AHW1	3300*	2200	HW	HW	30/12	623 (283)	\$12,099
ON3305AHW2	3300*	2200	HW	HW	75/30	761 (345)	\$13,135
ON3305AHW4	3300*	2200	HW	HW	191/76	1117 (507)	\$16,673
ON3305AHW6	3300*	2200	HW	HW	327/131	1622 (736)	\$17,267
ON3305AHW8	3300*	2200	HW	HW	477/191	1978 (897)	\$19,155
ON3305AHW10	3300*	2200	HW	HW	641/257	2334 (1059)	\$21,709
ON5000AHW0	5000	3400	HW	HW	**	405 (184)	\$9,833
ON5000AHW1	5000	3400	HW	HW	47/21	623 (283)	\$12,004
ON5000AHW2	5000	3400	HW	HW	118/53	761 (345)	\$13,391
ON5000AHW4	5000	3400	HW	HW	295/132	1117 (507)	\$17,950
ON5000AHW6	5000	3400	HW	HW	504/226	1622 (736)	\$18,544
ON5000AHW8	5000	3400	HW	HW	737/331	1978 (897)	\$20,476
ON5000AHW10	5000	3400	HW	HW	989/444	2334 (1059)	\$23,054

<sup>\*</sup> These models are hot-swap, field-upgradeable to 5000 VA.

<sup>\*\*</sup> To add runtime, see battery cabinet information on page 15. Runtimes are based upon fully charged, new batteries. Runtimes are affected by battery age, ambient temperature, site-specific UPS usage patterns, and actual operating load characteristics. Actual runtimes may vary.

<sup>^</sup>Full maintenance bypass allows hot-swap of both the control and power modules

All ON Series Models have basic and advanced communications capabilities.

ONEAC ON Series 3300/3305/5000 systems are shipped on pallets 51" (H) x 27" (W) x 32" (D)

For UPS Communications, Software, and Accessories see page 10.

For ON Series 3.3 and 5.0 kVA UPS Options and Accessories, see page 16.



# ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)

ONEAC uses batteries and cabinets built specifically for applications that require extended, reliable power in a compact design. Combined with ONEAC's efficient UPS design, maintenance-free batteries and UL approved cabinet, the ON Series 3.3 - 5.0 kVA UPS models are ideal for space restricted areas and meet the rigorous demands for quality and safety.

# ONEAC ON Series 3.3 - 5.0 kVA UPS Line-Up and Match Battery Cabinets\* This product will be discontinued October 2007.

All cabinets include hot-swap battery serviceability, wheeled base, extendible battery ability, and connector accessories. Contact ONEAC for proper battery cabinet selection.

		Product	Ship Wt.	
ONEAC Part #	Description	<b>Dimensions</b>	lbs. (kg)	<b>List Price</b>
ONXBC-2C1017	ONEAC 3.3-5.0kVA Battery Cabinet with 1 string	17x22x22	360 (163)	\$3,451.00
ONXBC-2C2017	ONEAC 3.3-5.0kVA Battery Cabinet with 2 strings	17x22x22	500 (227)	\$5,230.00
ONXBC-4C3017	ONEAC 3.3-5.0kVA Battery Cabinet with 3 strings	17x22x39	720 (327)	\$6,202.00
ONXBC-4C4017	ONEAC 3.3-5.0kVA Battery Cabinet with 4 strings	17x22x39	860 (390)	\$6,643.00
ONXBC-6C5017	ONEAC 3.3-5.0kVA Battery Cabinet with 5 strings	17x22x57	1090 (494)	\$7,929.00
ONXBC-6C6017	ONEAC 3.3-5.0kVA Battery Cabinet with 6 strings	17x22x57	1230 (558)	\$8,921.00

ONEAC ON Series 3.3 - 5.0 kVA UPS Battery Cabinets for Additional Runtime - Call factory



# ONEAC ON Series UPS (Power Conditioned, Line-Interactive) (continued)

### ONEAC ON Series 3.0 and 5.0 kVA Options/Accessories This product will be disconinued October 2007.

ONEAC Part #	Description	Factory Installed	Ship Wt. Ibs. (kg)	List Price
ON5000CM60	ON3305 Upgrade module for 5000 VA/3400 Watt capacity	*	50 (23)	\$1,708.00
CA-NTMERIDIAN	8' cable for interface to Nortel Meridian	NO	1 (.5)	\$49.00
CA-NTMERIDIAN45	45' cable for interface to Nortel Meridian	NO	1 (.5)	\$249.00
305-131	10' Input Plug for ON3300 (L6-30P)	NO	10 (5)	\$139.00
305-157	10' Input Plug for ON3305 and ON5000 (L6-50P)	NO	10 (5)	\$239.00
ONRACK	RackBuilder Kit for ON 3.3 and 5.0 kVA	NO	68 (31)	\$600.00
ONSEISMIC-2H-U	2 High Seismic Bracket Kit for ON 3.3 and 5.0 kVA UPS	NO	15 (7)	\$225.00
ONSEISMIC-3H-U	3 High Seismic Bracket Kit for ON 3.3 and 5.0 kVA UPS	NO	19 (9)	\$250.00
ONSEISMIC-2H-B	2 High Seismic Bracket Kit for ON 3.3 and 5.0 kVA Battery	NO	18 (8)	\$225.00
ONSEISMIC-3H-B	3 High Seismic Bracket Kit for ON 3.3 and 5.0 kVA Battery	NO	25 (11)	\$250.00

<sup>\*</sup> The ON3305 models are hot-swap, field-upgradeable to 5000 VA, but can be factory installed.



## **Connectivity Software and Accessories**

Unattended Shutd	lown and Management		
ONEAC Part #	Description	Ship Wt. Lbs. (kg)	List Price
SK-PROMOP-O	For ON Series UPS - MopUPS® Professional Software Kit for Intel-Based Systems (includes software and cable). Compatible w/Windows NT/2000/XP/(ME)/98/95, Novell Netware v4.x & 5.1, Redhat Linux and Unix	1 (.5)	\$99.00
SK-PROMOPRU-O	For ON Series UPS - MopUPS® Professional Software Kit for RISC and Intel based OS (includes software and cable).  Compatible w/Sun Solaris (2.5 and up), HP UX (11.0), and IBM AIX (4.3.2) and Windows NT/2000/XP/(ME)/98/95, Novell Netware v4.x & 5.1, Redhat Linux, Unix, SCO.	1 (.5)	\$178.00
SL-PROMOP25	MopUPS Professional Site License 25 users	0	\$1525**
SL-PROMOP50	50 users	0	\$2760**
SL-PROMOP100	100 users	0	\$4968**

<sup>\*\*</sup> Non-discountable items.

D	te Manac	
24 (2) (1 ( ) )		

ONEAC Part #	Description	Ship Wt. Lbs. (kg)	List Price
AM-P1-OL	ManageUPS®NET SNMP/WEB Adapter Kit for Vintage ON Series UPS (V96) (adapter & software)	1 (.5)	\$499.00
AM-VP-O	ManageUPS®NET SNMP/WEB Adapter Kit for ON Series Universal Mount UPS (ON700, ON1000, ON1500 and ON2000) & Sinergy II Series UPS (adapter & software)	1 (.5)	\$399.00
AME-P1-O	ManageUPSNET SNMP/WEB Adapter Kit with evironmental probe for ON Series Universal Mount and Sinergy S II and SE II Series UPS (adapter & software)	1 (.5)	\$640.00

#### Communication Cables and Accessories for Systems with Native UPS Monitoring Capabilities

		Ship Wt.	
ONEAC Part #	Description	Lbs. (kg)	List Price
CA-4CP3S-02	Interface Cable for ON Series m UPS		\$8.00
CK-ONEPLUS	Y-Cable for multi-server shutdown	2 (.9)	\$69.00
CA-9F	6 Foot DB9F-DB25F Serial Port Cable	32 (15)	\$39.00
CA-AS400B	6 Foot DB25F-DB15M Serial Port Cable	1 (.5)	\$39.00
AK-NTMERIDIAN	For Nortel Networks Apps- isolated contacts card and 8' cable connects ON Series UPS to system monitor port J4 in master column of PBX	5 (2)	\$119.00



### **Replacement Battery Plans**

#### Replacement Battery Packs and Cabinets for ONEAC UPSs

Replacement battery packs are original equipment, pre-wired battery packs with installation instructions, return shipment carton, prepaid return freight and a 2-year warranty. Return used batteries to ONEAC for trouble-free

		Ship Wt	
<b>ONEAC Part #</b>	Battery Pack Description	lb. (kg)	List Price
ONEPLUSBP-107	Replacement Battery Pack for ONE254	6 (3)	\$93
ONEPLUSBP-109	Replacement Battery Pack for ONE404	6 (3)	\$104
ONEPLUSBP-207	Replacement Battery Pack for ONE604	14 (6)	\$180
ONEPLUSBP-307	Replacement Battery Pack for ONE1004	20 (9)	\$205
ONEBP-210	Replacement Battery Pack for ONe200D Models	10 (5)	\$100
ONEBP-107	Replacement Battery Pack for ONe200, ONe300, ONm300 Models	7 (3)	\$70
ONEBP-207	Replacement Battery Pack for ONe300D, ONm300D, ONe200x-W/M, ONe300X-W/M Models	13 (6)	\$157
ONBP-204	Replacement Battery Pack for ON400 (v96)*, ON280 (v92)	8 (4)	\$142
ONBP-207	Replacement Battery Pack for ON600 (v96* or v92), ON400XR, ONe400D, ONe600X, ONm600X Models	13 (6)	\$168
ONBP-405	Replacement Battery Pack for ON700, ON1000, ON1500; for ON2000 (Qty 2 Required) Universal Mount Models	19 (9)	\$365
ONBP-407	Replacement Battery Pack for ON900 (v92) Models	26 (12)	\$306
ONBP-410	Replacement Battery Pack for ON900 (v96)* Models; for ON20000X-4U-SN, ON2000X-4U-4N (internal, qty 2 required)	19 (9)	\$281
ONBP-517	Replacement Battery Pack for ON3300, ON3305, ON5000 Models (Qty 2 required) - replaces one string (10 batteries)	73 (33)	\$821
ONBP-607	Replacement Battery Pack for ON1300 (v92) Models	37 (17)	\$533
ONBP-217	Replacement Battery Pack for ON1300 (v96)*, ON400X-WL, ON600X-WL Models; for ON2000X-SR-SN (internal, qty 2 required)	30 (14)	\$280
ONBP-807	Replacement Battery Pack for ON2000 (v92) Models	49 (22)	\$629

		Ship Wt	
ONEAC Part #	Battery Cabinet Description	lb. (kg)	List Price
ONEXBC-W-217R**	Replacement Battery Cabinet for ONe200X-WM, ONe300X-WM Models (ext. battery cabs.)	38 (17)	\$325
ONEXBC-217R**	Replacement Battery Cabinet for ONe600X, ONm600X Models (ext. battery cabs.)	60 (27)	\$325
ONBC-417R**	Replacement Battery Cabinet for ON2000 (v96)* Models	74 (34)	\$692
ONXBC-417R**	Replacement Battery Cabinet for ON600X, ON900X, ON2000X, ON2200X Models	74 (34)	\$695
ONBC-RM-417R**	Replacement Battery Cabinet for ON2000-RM (v96)* Models	84 (38)	\$890
ONXBC-SR-417R**	Replacement Battery Cabinet for ON2000X-SR-SN, ON2000X-4U-SN, ON2000X-4U-4N Models (ext. bat. cabs.)	79 (36)	\$890
ONXBCU-417R**	Replacement Battery Cabinet for ON700, ON1000, ON1500, and ON2000 Universal Mount Mode	82 (37)	\$690

 $<sup>^{\</sup>star}$  V96 models have 'N' (A-SN or I-SN) in the UPS part number, i.e.: ON400A-SN

#### 5-Year Extended Battery Warranty for ON Series and Sinergy Series UPSs - call factory

<sup>\*\*</sup> New batteries installed in remanufactured battery cabinet. A deposit of \$225 (part number RBP-DEP) will be billed to the customer and credited when the old battery is received in